

Bid Specification

Video Monitoring and Documentation

ConstructionCam Lite

Fast, dependable, solid state Linux operating system

256bit AES encrypted onboard storage

Edge Video Recorder (EVR) - up to 120 days of continuous security video recording

10/100 ethernet or transmit over 4G networks



All weather dome housing with heater and fan

User controllable 360° robotic Pan/Tilt/Zoom camera with multiple preset composition

16:9 full-frame live HD video
40x optical, 12x digital zoom


2.1 MP archives presets: 1920 x 1080 pixels

Automatic day and night function

Specification includes camera system and managed services



User Controllable



Current and Historical Weather Data



iOS and Android App



Website and Facebook Integration



Installation and Maintenance



Quality Control and Maintenance



Full Service Support



AI-Edited Time-Lapse Movies

Additional services included



EarthCam.net
The Webcam Technology Experts

1-800-EARTHCAM
www.earthcam.net/contactus



01.32.36 Video Monitoring and Documentation Bid Specification

1. The Contractor shall provide a High Definition Robotic Streaming Video Webcam for users to remotely control and view a live feed via a secure connection via a network connection. The camera will provide a full view of the work area on the construction site.

CONTACT SYSTEM VENDOR: EarthCam / Brian Cury +1 201.488.1111 Email: WWW.EARTHCAM.NET/CONTACTUS

2. The camera shall meet or exceed the following requirements:
 - 2.1 Consist of all-weather aluminum housing with an polycarbonate clear dome
 - 2.2 User controllable Pan/Tilt/Zoom controls with multiple preset compositions
 - 2.3 Live streaming 16:9 1080p HD video
 - 2.4 40x optical, 12x digital zoom with endless pan angle of 360°
 - 2.5 Automatic Day and Night function
 - 2.6 H.264 and Motion JPEG video compression
 - 2.7 Up to 50/60fps in 1080p
 - 2.8 2.13 Megapixel images (1920 x 1080 pixels)
 - 2.9 Communications: RJ-45 10BASE-T/100BASE-TX PoE
 - 2.10 4G cellular modem
 - 2.11 High Power over Ethernet (High PoE), max. 17 W
 - 2.12 Secure 256 bit AES encrypted onboard storage
 - 2.13 High-Definition continuous video recording with 7 days of retention (up to 120 days available)
 - 2.14 Industrial grade solid state embedded Linux System
 - 2.15 120VAC, 220-230VAC or 12VDC power
 - 2.16 Designed for EarthCam Control Center Software
3. Internet Based Online Interface: The camera will be accessible via an internet based Software as a Service (SaaS) solution. This online interface will be managed and supported by the System Vendor. The service will be available for the term of the project and allow the viewing of live video and High Definition digital still images captured and stored of the project on both mobile and desktop platforms.

The Internet Based Online Interface shall include the following features:

- 3.1 Responsive HTML5 design for cross-platform access on desktop and mobile devices
 - 3.2 Secure HTTPS compliant with live stream secured & encrypted via https transport
 - 3.3 Display project name and logo
 - 3.4 Project Dashboard allows easy navigation between multiple cameras and projects
 - 3.5 Security Interface offers flexible multi-view camera grid selective up to 9 cameras per screen streaming simultaneously
 - 3.6 Edge Video Recorder features intuitive visual timeline interface for fast incident footage retrieval and sharing
 - 3.7 Real-time live video viewing with user-controllable Robotic Pan, Tilt and Zoom
 - 3.8 User-controllable settings for creating and editing multiple preset compositions, each preset will be displayed as a thumbnail image
 - 3.9 Picture in picture capability for viewing live video and High Definition images simultaneously
 - 3.10 Instant live snapshot capability in addition to preset scheduled archives
 - 3.11 Visual timeline with quick thumbnail view allows image navigation by year, month, day and hour
 - 3.12 AI-edited time-lapse technology removes frames obscured by foreign objects or weather elements, with music and graphics then added for downloadable presentations
 - 3.13 Full Screen Mode for displaying video and complete image without any graphical frame
 - 3.14 Photo Filters and Graphical Markup Tools for detailing and creating notes with graphical overlays on images, including project title, logo and time date stamp
 - 3.15 Image Comparison Tool for comparing two images taken at different times, overlaid on top of each other
 - 3.16 Share Image Tool for saving, printing, emailing and posting to Hall of Fame
 - 3.17 Project Management Software integration (Aconex, Autodesk BIM 360, PlanGrid, Procore, SharePoint)
 - 3.18 3D/4D Model Integration (Autodesk Navisworks and Revit, Bentley Synchro)
 - 3.19 Social Media Integration Tools for sharing project images and notes on Facebook and Twitter
 - 3.20 Automatically generated daily/weekly project progress update email with camera image and weather
 - 3.21 Graphical Weather applet displaying local weather data with satellite and updating radar imaging
 - 3.22 Integration of maps, aerial and satellite imagery
 - 3.23 Graphical Data Management Tools showing archived and current system status of solar amperage, battery power remaining, wireless radio connectivity, and device location
 - 3.24 Automatically generated Progress Reports (in PDF and PowerPoint formats) using weekly camera images with associated weather data, notes, and client logo
4. Access to account protected by Account Security feature which includes four levels of password protection, IP address block/permission and SSL protection of user login password.
 5. The system shall capture and upload images every 5 minutes, 24 hours per day.
 6. The system shall have M2M – Machine to Machine 24/7 Support with active self-healing technology and automatic software upgrades to maintain the quality, consistency and reliability of all images.
 7. Images will be maintained on the System Vendor's servers for reference available at all times during the life of the project and for no less than 60 days after completion. All images will be protected on servers owned and operated by the System Vendor and located in a secure area at the System Vendor's location.
 8. The Contractor shall provide all service and maintenance, including cleaning, of the camera system throughout the life of the project including making appropriate arrangements for camera to remain in operation up to and through finalization of all structural, landscaping and "completed state" condition necessary for beginning-to-end time-lapse record.
 9. The System Vendor shall provide a scalable, responsive, cross-platform camera media viewer. Camera viewer to include 40 features with capability to be personalized based on client preference for a total of 720 customizable options. Viewer shall be delivered via embed code or in a standalone web page. Additional features include instant access to AI-Edited, presentation-ready videos, Facebook and Twitter social media integration, full screen mode, image comparison, weather data, multiple logos, graphical background images and customizable project description.
 10. The System Vendor at the end of the project shall provide a comprehensive archive package that includes all images, historical weather data, AI-edited time-lapse videos and a royalty-free web-based viewer software. The software shall include the same interactive interface as the live camera during the project.
 11. The System Vendor shall provide hand-edited time-lapse movie(s) at the end of the project. Time-lapses shall be professionally edited by a video editor using image stabilization software. The movie will start with an appropriate music track, custom graphic, incorporating your project title and company logos. Periods of bad weather or inactivity shall be removed to produce a compelling and consistent movie from start to finish. A machine edited movie will not be acceptable.
 12. The Contractor shall secure a nearby structure for camera mounting or provide a fixed pole (40 foot / 12 meters height recommended) and 3 inch / 8 centimeters minimum diameter as per System Vendor's instruction. The Contractor shall supply all equipment required for safe and secure access to the camera location for technicians performing installation and maintenance services, including building access, bucket truck and/or lift. The System Vendor will consult on and provide recommendations for optimal camera placement and provide professional installation services as required.